

FERREX®

The settings below follow testing by SCS Spreader & Sprayer Testing Ltd.

They should be regarded as indicative and users should follow appropriate calibration regimes for their machines and allow for field conditions in order to achieve a good spread.

Machine	Disc / Vane Type	Spreader Height / Tilt	Rate Kg/ha	Disc Speed	Spread Width	Spread Setting
Bullock T24	275 mm	110 cm 0*	6	No. 12	12 m	Centre
		110 cm 0*	6	No. 15	18 m	Centre
		110 cm 0*	6	No. 30	24 m	Centre
		110 cm 0*	6	No. 30	28 m	Centre
Logic TFS80P	3 vane deep	100 cm 0*	6	3000	12 m	5.5
		100 cm 0*	6	3000	18 m	10
Spaldings Lehner Super Vario	2 vane vario	100 cm 0*	6	3000	12 m	2 & 3
		100 cm 0*	6	3000	15 m	2 & 3
Stocks Ag Fan Jet Pro 65	2 vane	110 cm 0*	6	No. 6	12 m	90
		110 cm 0*	6	No. 12	18 m	90
		110 cm 0*	6	No. 12	20 m	90
Stocks Ag Fan Jet Duo	2 long 2 short	150 cm 0*	6	No. 8	12 m	105
		150 cm 0*	6	No. 10	18 m	105
		150 cm 0*	6	No. 12	24 m	105
		250 cm 0*	6	No. 12	30 m	105

Sipcam UK Ltd

4c Archway House, The Laterns, Melbourn Street,

Royston, UK SG8 7BX

T: +44 (0)1763 212 100 F: +44 (0)1763 212 101

www.sipcamuk.co.uk

Always Read The Label. Use pesticides Safely

'Ferrex' contains Ferric Phosphate

